

## DEHYDROLUBE

This nonflammable lubricant is a combination of special water displacement compounds, corrosion inhibitors, solvents, nongreasy lubricants, and P.T.F.E. It is used to displace water and moisture from electrical equipment such as contact points and automotive distributors, machinery parts, guns and equipment. This lubricant is used by factories, truck lines, delivery services, transit systems, schools, machine shops, service stations, air lines, maintenance shops and general industries. Contains no ozone depleters.

**IMPORTANT:** Conforms to Military Specification Mil-C-23411 for corrosion prevention.

### DIRECTIONS:

Keep actuator pointed towards do ton valve cup. Remove cap. Direct spray toward area to be treated and spray liberally until all moisture is rinsed away. This will also leave a protective coating to repel moisture. Repeat as needed. Can also be used to loosen rusty nuts and bolts.

**CAS Numbers:** Contains Perchloroethylene (127-18-4), Oil(64742-65-0), 2-Butoxyethanol (111-76-2), Carbon Dioxide (124-38-9).

**GMP**  
Chemical Solutions

A391

## GENERAL MAINTENANCE PRODUCTS

## DEHYDROLUBE

### Penetrating Lubricant & Moisture Displacement Agent

- Excellent Rust-Buster
- Moisture Displacement
- Corrosion Preventer
- Nonflammable
- 4 in 1 Penetrating Oil

#### WARNING:

VAPOR HARMFUL. CONTENTS UNDER PRESSURE. KEEP OUT OF REACH OF CHILDREN. See additional cautions on back panel.

NET WT. 15 OZ. (425 grams)

#### WARNING:

Vapor harmful. Contains Perchloroethylene and 2-Butoxyethanol. Use with adequate ventilation to keep exposure levels below the 25 parts per million O.S.H.A. permissible exposure limit (PEL) during an eight hour period (time weighted average). Consult the product material safety data sheet for additional information regarding exposure concerns. Avoid inhalation of spray mist or vapors. If overcome by fumes, remove victim to fresh air. Resuscitate if necessary. Get medical attention. Avoid contact with eyes and skin. In case of eye contact, flush immediately with plenty of water and continue for 15 minutes. If discomfort persists, see a physician. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. **WARNING:** This product contains a chemical or chemicals known to the State of California to cause cancer.

#### KEEP OUT OF REACH OF CHILDREN



Reorder A391  
800-548-2080

| HMIS RATING              |
|--------------------------|
| 2 - HEALTH               |
| 2 - FLAMMABILITY         |
| 0 - REACTIVITY           |
| B - PROTECTIVE EQUIPMENT |

SOLD EXCLUSIVELY BY:

  
General Products & Supply Inc.

**GMP**  
Chemical Solutions

Murrysville Business Park  
Export, PA 15632

101 Technology Lane  
(800) 548-2080