

R.I.V. is a proven insulator spray with dielectric strength up to 1,000 volts per mil. With high arc resistant coating impregnates and insulates. **R.I.V.** provides excellent adhesion to windings, coils, and metals. Dries quickly protecting surface against oils, moisture, acid, and alkalies.

DIRECTIONS

1. Shake until ball inside can breaks loose and rattles. Then shake for at least one minute.
2. Spray at room temperature (approximately 70°F).
3. Surface must be free of grease, rust, dirt, and wax.
4. Mask off or protect other areas from the overspray.
5. Hold can about 10 to 12 inches away from object to be sprayed.
6. Two thin coats are recommended rather than one heavy coat. Apply second coat as soon as first coat is dry.
7. After spraying, turn can upside down and press sprayhead for about three seconds. This will clean paint from siphon tube and valve.

CAS Numbers: Contains Toluene (108-88-3), Acetone (67-64-1), 1,1,1, Trichloroethane (71-55-6), Xylene (1330-20-7), Propane (74-98-6), Isobutane (75-28-5), n-Butane (106-97-8).



GENERAL MAINTENANCE PRODUCTS



CAUTION

Contents under pressure. Exposure to heat may cause bursting. Do not spray near heat, sparks, or open flame. Use with adequate ventilation. Avoid breathing spray mist and vapor. Deliberately concentrating and inhaling the vapor of contents may be harmful or fatal. Avoid frequent or prolonged contact with skin and eyes. Do not store at temperatures above 120°F. Do not place near source of heat, radiator, or direct sunlight. High temperatures may cause the container to burst.

FIRST AID

IF IN EYES: Flush thoroughly with water for 15 minutes. Get medical help.

IF ON SKIN: Wash affected area with soap and water.

IF INHALED: Provide oxygen or fresh air.

IF SWALLOWED: Do not induce vomiting. Call a physician immediately.

KEEP OUT OF REACH OF CHILDREN



Reorder A397
800-548-2080

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

Murrysville Business Park
Export, PA 15632

HMIS RATING
4 - FLAMMABILITY
2 - HEALTH
0 - REACTIVITY
A - PERSONAL PROPERTY


GMP
Chemical Solutions

101 Technology Lane
(724) 327-7200