QUICK SEAL is ideal for use wherever a strong, permanently elastic, weatherproof adhesive, sealant, or caulking is needed. This product has excellent adhesion characteristics, high chemical resistance and will not sag or shrink due to severe temperature extremes.

QUICK SEAL can be used for sealing cracks in machinery, heating and ventilating duct work, plumbing fixtures, electrical connections, low pressure water and drain pipes. This product bonds nameplates, machinery flanges, glass, signs and electrical insulation, etc. Ideal for caulking windows, doors, walls, ceiling cracks and crevices. Forms in-place gaskets. Paint will not adhere to cured material.

This product meets Federal Specs TT-S-001543, Class A; TT-S-00230, Class A (COM-NBS).

DIRECTIONS

For best adhesion, surface must be clean, dry, and free of oil, tar, dirt and dust. A 1/16" to 1/8" bead dries in one hour, cures in 24 hours and reaches optimum strength in 7 days.

After each use, leave a small bed of material on the can, which will form a sealing plug, for reuse. To use, gently pull the plug and begin to use the material. If plug breaks, leaving the dispensing tip sealed, use a paper clip or other wire object to remove and loosen the remainder of the cured material.

Contains: Amorphous Silica (CAS #7631-86-9), Methyltriacetoxysilane (CAS #4253-34-3), Ethyltriacetoxysilane (CAS #17689-77-9) and Liquified Petroleum Gas (68476-85-7).



A591

GENERAL MAINTENANCE PRODUCTS

QUICK SEAL WHITE

Silicone Sealer, Caulking, and Adherive

- 100% RTV Silicone, Industrial Strength
- Temperature Range -60°F to +500°F
- Caulks Around Tubs, Sinks And Showers
- Insulated Electrical Components
- Seals Around Windows, Doors, Walls, Etc.
- Bonds Most Materials, Similar Or Dissimilar (Glass, Wood, Metal, Rubber, Plastic, Ceramics, etc.)
- Mildew Resistant Formula

KEEP OUT OF REACH OF CHILDREN NET CONTENTS: 7.25 oz (205 g)

CAUTION

Use with adequate ventilation. Product releases acetic acid (vinegar like odor) during curing. Contact lens wearers take appropriate precautions. Contents under pressure. Do not puncture or incinerate. Do not store at temperatures above 120°F (50°C). Do not store in automobiles, in direct sunlight or any area with temperatures above 120°F.

FIRST AID

In case of eye contact, immediately flush with water for 15 minutes. CALL A PHYSICIAN IMMEDIATELY. In case of contact with skin, wipe off excess sealant with dry paper towel or cloth, and wash with soap and water.

KEEP OUT OF REACH OF CHILDREN



Reorder A591 800-548-2080



SOLD EXCLUSIVELY BY:





Murrysville Business Park Export. PA 15632 101 Technology Lane (724) 327-7200