sprays out of the can as a thin, penetrating liquid and quickly becomes a thick, red grease capable of clinging to vertical surfaces. Additives provide superior adhesive, cohesive, extreme pressure and cushioning properties. This formula lubricates and prevents oxidation and rust without the dangers of ozone depleting, chlorinated solvents.

# Contains NO Chlorinated Solvents (NO 1,1,1-Trichloroethane)

### **USE ON:**

Wire rope, open gears, linkages, draglines, fittings, winches, cranes, cams, valves, cables hoists, pulleys and rollers.

### **DIRECTIONS**

SHAKE WELL BEFORE USING. Spray first up close to flush off old grease and dirt build up. Then spray a thin film on surface to be lubricated. Liquid will creep and penetrate then gel in approximately 20 minutes.



A727

### GENERAL MAINTENANCE PRODUCTS

## SURE LUBE

Multi-Purpose Red Grease
Lubricant

\*New Generation

- Penetrates As A Liquid, Then Quickly Sets Up
- Withstands Heat To 500°F
- Resists "Throw Off"

#### DANGER:

EXTREMELY FLAMMABLE.
VAPOR HARMFUL.
HARMFUL OR FATAL IF SWALLOWED.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL

**DANGER:** Contains Isoparaffinic Hydrocarbon (64741-66-8), Lithium Grease (N/A) and Liquified Petroleum Gas (68476-85-7). Use only in a well ventilated area. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

### **KEEP OUT OF REACH OF CHILDREN**

### FIRST AID:

**EXCESSIVE INHALATION:** Remove to fresh air and call a physician.

**IF IN EYES:** Flush with water for 15 minutes, lifting upper and lower lids. Get medical attention.

**IF SWALLOWED:** Do not induce vomiting. Get medical attention immediately.

**IF ON SKIN:** Wash affected area immediately with soap and water. If irritation persists, get medical attention.



Reorder A727 800-548-2080



SOLD EXCLUSIVELY BY:





Murrysville Business Park Export, PA 15632

101 Technology Lane (800) 548-2080