

## MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA's Hazard Communication Standard CFR 1910.1200 and OSHA Form 174.

N/A SIGNIFIES NON-APPLICABLE

## IDENTITY AND SUPPLIERS INFORMATION

PRODUCT NAME:	DEGREASEALL L-VOC	CHEMICAL FAMILY:												
GMP PRODUCT NUMBER:	A735	FORMULA:	PROPRIETARY	<table><tr><th>HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM</th><th>RATING</th></tr><tr><td>HEALTH</td><td>2</td></tr><tr><td>FLAMMABILITY</td><td>3</td></tr><tr><td>REACTIVITY</td><td>0</td></tr><tr><td>MAX PERSONAL PROTECTION</td><td>B</td></tr></table>	HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	RATING	HEALTH	2	FLAMMABILITY	3	REACTIVITY	0	MAX PERSONAL PROTECTION	B
HMIS HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	RATING													
HEALTH	2													
FLAMMABILITY	3													
REACTIVITY	0													
MAX PERSONAL PROTECTION	B													
SUPPLIER'S NAME:	GENERAL PRODUCTS & SUPPLY, INC.	PHONE NUMBER:	(724) 327-7200											
SUPPLIER'S ADDRESS:	101 TECHNOLOGY LANE	EMERGENCY NO.:	800-255-3924											
	EXPORT, PA 15632	DATE PREPARED:	11/16/10											
PROPER SHIPPING NAME:														

## SECTION 1 - INGREDIENT IDENTIFICATION AND INFORMATION

CHEMICAL NAME	CAS NO.	OSHA PEL	WT %	SARA III	PEL	TLV	ACGIH TLV
Acetone	67-64-1					500 ppm	
Toluene	108-88-3					20 ppm	
Propane	74-98-6					2500 ppm	
Xylene	1330-20-7					100 ppm	
Ethylbenzene	100-41-4						

## SECTION 2 - PHYSICAL/CHEMICAL PROPERTIES

## SECTION 3 - FIRE/EXPLOSION HAZARD DATA

BOILING POINT:	<0 to 292°F	FLAMMABILITY: (FLAME PROJECTION)	AUTO IGNITION TEMP:
VAPOR PRESSURE: (mm Hg)		FLASH POINT: <0°F	
VAPOR DENSITY:	Heavier Than Air	FLAMMABILITY LIMITS:	%UEL: 12.8 %LEL: 1.0
SOLUBILITY IN WATER:	Not Applicable	EXTINGUISHER MEDIA:	Use water fog, dry chemical or carbon dioxide.
SPECIFIC GRAVITY:	0.74 + 0.05	SPECIAL FIRE FIGHTING PROCEDURES:	Aerosol cans may rupture when heated.
pH RANGE:	Not Applicable	UNUSUAL FIRE/EXP. HAZARDS:	Heated cans may burst.
VOC:	45%		
EVAPORATION RATE: (Ether=1)	Slower Than Ether		
PHYSICAL DESCRIPTION:	Clear colorless liquid with an aromatic odor.		

## SECTION 4 - REACTIVITY HAZARD DATA

STABILITY:	Stable
HAZARDOUS POLYMERIZATION:	Will Not Occur
INCOMPATIBILITY:	None Known
CONDITIONS TO AVOID:	High Temperatures
HAZARDOUS DECOMPOSITION PRODUCTS:	In fire, will decompose to carbon dioxide, carbon monoxide.

## SECTION 5 - HEALTH HAZARD DATA AND FIRST AID

PRIMARY ROUTES OF ENTRY:		FIRST AID PROCEDURES:	
ACUTE EFFECTS:		SKIN:	Immediately flush exposed area with water for at least 15 minutes. If irritation persists get medical attention. Remove contaminated clothing and launder before reuse.
SKIN:	Skin irritant. Will cause defatting of skin. Effects are reversible.	EYES:	Immediately flush with large quantities of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Seek medical attention.
EYES:	Eye irritant. Will cause redness and burning sensation.	INHALATION:	Remove person to fresh air. If irritation persists, give oxygen, get medical attention.
INHALATION:	Effects of overexposure include irritation of respiratory tract, headache, dizziness, nausea, and loss of coordination. Extreme overexposure may result in unconsciousness and possibly death.	INGESTION:	DO NOT induce vomiting. Seek medical attention immediately. Keep person warm and quiet.
INGESTION:	Aspiration hazard if swallowed.		

## SECTION 6 - CONTROL AND PROTECTIVE MEASURES

RESPIRATORY PROTECTION:	Self-contained breathing apparatus if above TLV limit.
PROTECTIVE GLOVES:	None required if spraying.
EYE PROTECTION:	We recommend the use of safety glasses or chemical splash goggles.
VENTILATION REQUIREMENTS:	Provide local exhaust to keep TLV of Section 1 ingredients below acceptable limit.
OTHER PROTECTIVE EQUIPMENT:	Long sleeves and long pants.
HYGIENIC WORK PRACTICES:	Do not eat, drink or smoke in work area. Wash hands after handling. Launder contaminated clothing.

## SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:	Use absorbent sweeping compound to soak up material. Put into container. Dispose as hazardous waste.
WASTE DISPOSAL METHODS:	Dispose as hazardous waste in accordance with EPA RCRA.
PRECAUTIONS IN HANDLING AND STORAGE:	When spraying more than one half can continuously or more than one can consecutively, use NIOSH approved respirator. Store at temperatures below 120°F. Keep away from heat, sparks, or open flame. For industrial and institutional use only. For use by trained personnel only. Keep container closed during storage.
OTHER PRECAUTIONS:	KEEP OUT OF REACH OF CHILDREN.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without any warranty or guarantee of any kind.