

**RUSTECH** represents a breakthrough in polymer technology which will save time, money and labor. Hours of labor required to remove rust from structures, machinery, vehicles and equipment can now be eliminated. **RUSTECH** provides long-term protection to iron and steel surfaces when used with a single application of oil-based paint. **RUSTECH** is easy to apply, offers easy surface preparation and ease of clean-up.

**RUSTECH** chemically stops rust and converts it into a hard, black, paintable coating. There is no longer a need to clean rusted metal to a bright surface for further protective treatment.

#### DIRECTIONS

Shake well before use. Remove grease, oil and dirt from the surface (wire brushing may be required to remove flaky rust, loose scales or blistered paint). The surface should be 50°F or warmer.

Apply **RUSTECH**, as supplied, using a brush, roller or airless sprayer. A black coating will form over the rusted areas only. A second coat should be applied for best protection.

**RUSTECH** fully cures in approximately 24 hours. **RUSTECH** may be topcoated within 48 hours with oil based paints. Seal coating with two coats of a high quality oil-based paint. Coverage is 500 square feet per gallon on a smooth, non-porous surface. Irregular, porous or textured surfaces may require more product. Clean application equipment and cap threads with detergent and water. Do not return unused product to container.

**CAS NUMBERS:** Contains Proprietary Polymer...no CAS Number, Water 7732-18-5, Tannic acid 1401-55-4, 2-Butoxyethanol 111-76-2, Synthetic Smectite 53320-86-8

**Gmp**  
Chemical Solutions

C307

#### GENERAL MAINTENANCE PRODUCTS

## RUSTECH

### Corrosion Control for Rusted Metal

- Easy surface preparation
- Converts rusted metal to non-rusting surface
- Safe and nonflammable

**CAUTION:** Harmful if swallowed. Severe eye irritant. See side panel for additional precautionary information.

**KEEP OUT OF REACH OF CHILDREN.**

NET CONTENTS 32 OZ(S)

#### CAUTION

Harmful if swallowed. Avoid contact with eyes and mucous membranes. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. In case of spillage, absorb with inert material and dispose in accordance with applicable regulations.

#### FIRST AID

**IF IN EYES:** Flush eyes and under eyelids with cool water for at least 15 minutes. Obtain medical attention.

**IF SWALLOWED:** Give person several glasses of water and induce vomiting. Obtain medical assistance immediately.

**IF ON SKIN:** Remove contaminated clothing and launder before re-use. Wash out product quickly with soap and water.

**IF INHALED:** If breathing difficulty is observed, remove person to fresh air.

#### KEEP OUT OF REACH OF CHILDREN



Reorder C307  
800-548-2080

#### HMIS RATING

0 - FLAMMABILITY

2 - HEALTH

1 - REACTIVITY

B - PERSONAL PROPERTY

SOLD EXCLUSIVELY BY:

  
General Products & Supply Inc.

Murrysville Business Park  
Export, PA 15632

**Gmp**  
Chemical Solutions

101 Technology Lane  
(800) 548-2080