

**ORANGSOL RTU** can be applied to machinery, floors, etc. that have a build-up of glues, gums, baked on greases, or other built-up soils. Regular uses keeps drains clean, deodorized and free flowing. Can be used to control odors around garbage disposal areas, septic tanks, kennels, etc. **ORANGSOL RTU** can be used in recirculating cold parts washers, for cleaning equipment, machinery, small parts, etc. where petroleum solvents pose safety, disposal, pollution, and toxicity problems. Numerous uses can be found where the strength of a petroleum solvent is needed without the disposal, pollution, and toxicity problems. Let your imagination create new uses for this product that has strong solvency properties with no disposal, pollution, or toxicity problems associated with petroleum solvents.

#### CAUTION:

This product is combustible in its concentrated form and should be stored in a cool place away from heat, sparks and open flame. Avoid eye contact and prolonged skin contact. Do not ingest.

**KEEP OUT OF REACH OF CHILDREN.**

#### FIRST AID:

**EYE CONTACT:** Flush with water for 15 minutes and get immediate medical attention.

**SKIN CONTACT:** Prolonged skin contact may remove natural oils and cause skin dryness. Wash with soap and water upon contact.

**IF SWALLOWED:** Get immediate medical attention.

**CAS NUMBERS:** Contains 4-isopropenyl-1-methylcyclohexene (5989-27-5) and nonionic surfactant (9016-45-9).



#### DIRECTIONS FOR USE:

**DEGREASING:** For heavy duty cleaning and degreasing, use full strength or cut 1 to 1 with water. Let stand several minutes and then rinse thoroughly. Dilution may vary with severity of soil and grease.

**FOR GLUE, GUM AND BUILD-UP REMOVAL:** Let set for several minutes and then rinse with warm water. (Note: test painted surfaces before using.)

**FOR DEODERIZING:** Add 4 Oz to a gallon of cold water. Can be applied by drip method of fogging around sewage treatment plants.

**DECLOGGING DRAINS:** Use weekly to keep drains free flowing and sanitary. Pour 8 Oz down drain, let stand 10 minutes, flush drain with hot water. If drain remains slow, repeat this process every 2 to 3 days.

**FOR COLD PARTS CLEANING:** Mix 1 part cleaner to 10 parts water to equal cleaning power of most petroleum based solvents.

**KEEP OUT OF REACH OF CHILDREN.**



Reorder C310  
800-548-2080

HMIS RATING	
1 - HEALTH	
1 - FLAMMABILITY	
0 - REACTIVITY	
B - PROTECTIVE EQUIPMENT	

SOLD EXCLUSIVELY BY:

  
General Products & Supply Inc.

Murrysville Business Park  
Export, PA 15632

**GMP**  
Chemical Solutions

101 Technology Lane  
(800) 548-2080