

**GREASE SOLVE** is a slime, odor, and grease controllant that quickly cuts through built-up grease. This powerful formula generates no heat and is safe on metal pipes. USDA authorized for use in federally inspected meat and poultry plants.

#### DIRECTIONS

**Built-up grease deposits:** mix four ounces to one gallon of warm water. Apply generously to greasy floors, walls, equipment, etc. with mop, sponge or rag. Allow to work for approximately five minutes, then rinse with clean water. The grease is effectively dissolved and becomes water rinseable.

**Odor control:** mix two ounces of **GREASE-SOLVE** to one gallon of cold water. Apply with sprayer to odor problem areas such as rubbish piles, dumpsters, garbage cans, etc. Odors are destroyed and the source for breeding of maggots in garbage areas is eliminated.

**Drain maintainer:** to open drains stopped by grease and slime build-up, pour a solution of one part product to four parts water. Allow to stand for one hour then flush with hot water. **GREASE-SOLVE** effectively dissolves grease, slime and soap scum deposits in drains, pipes, and grease traps.

**Grease traps and septic tanks:** to keep drain lines open, mix four ounces to one gallon of water. Pour into the drain and allow to stand for one hour. Flush with hot tap water. In garbage disposals, allow to stand five to 10 minutes, then flush with hot water.

**NOTE:** This is a powerful organic compound and may attack some plastic or painted surfaces. Test a small area before using. Since this formulation will effectively defat the skin, rubber gloves are recommended to prevent chapped conditions. This product is not corrosive to metal. Powerful solvent action will affect paint, linoleum and plastic. Do not use on resilient tile floors. Do not use in plastic plumbing pipes. Do not use on utensils, tables, etc. that are used for preparation or handling of food. Will not harm septic tanks or cesspools.

CAS Numbers: Contains citrus terpenes (68647-72-3), 2-butoxyethanol (111-76-2) and anionic surfactant (26264-05-1).



C964

**GENERAL MAINTENANCE PRODUCTS**

**GREASE-SOLVE**  
Slime, odor and grease  
controllant

- Cuts quickly through built-up grease
- Controls slime and odor
- Powerful formula generates no heat
- Safe on metal pipe
- Noncorrosive, nonacid, and noncaustic

**CAUTION:** Vapors may be harmful. See side panel for additional information.

**KEEP OUT OF REACH OF CHILDREN**  
NET CONTENTS 1 GALLON

#### CAUTION

Avoid contact with skin, eyes, and clothing. Do not take internally. Do not breathe vapors. Rinse empty container before discarding. This product is intended for industrial commercial use and storage by trained persons only. Manufacturer will not be responsible for any injury, loss, or damage if product is used in any manner not in compliance with label directions or if precautions are not observed.

#### FIRST AID

**IF IN EYES:** Flush with large amounts of water. Consult a physician if irritation persists.

**IF ON SKIN:** Flush with large amounts of water. Remove contaminated clothes. Seek medical attention.

**IF SWALLOWED:** Do not induce vomiting or give anything by mouth. Seek medical attention immediately.

#### KEEP OUT OF REACH OF CHILDREN



Reorder C964  
800-548-2080

HMIS RATING
2 - FLAMMABILITY
2 - HEALTH
0 - REACTIVITY
B - PERSONAL PROPERTY

SOLD EXCLUSIVELY BY:

  
General Products & Supply Inc.

  
GMP  
Chemical Solutions

Murrysville Business Park  
Export, PA 15632

101 Technology Lane  
(800) 548-2080