

TO4 TRANSMISSION FLUID is formulated for use in Caterpillar equipment specifying TO-4 fluids. In addition, it exceeds the performance requirements of Allison C-4 specifications.

TO4 TRANSMISSION FLUID is a recommended fluid for heavy-duty on-highway, and off-highway service requiring Allison C-4 or Caterpillar TO-4. It provides excellent service in all Caterpillar power shift transmissions, final drives, hydrostatic transmissions, torque converters, hydraulics and systems requiring TO-4 specified oils. It also meets the requirements of Komatsu Dresser and Eaton Transmissions.

PRECAUTIONS

Misuse of empty containers can be hazardous. Empty containers can be dangerous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion, or toxic fumes from residue. Do not pressurize or expose to open flame or heat. Keep container closed and drum bungs in place. Do not ingest.

KEEP OUT OF REACH OF CHILDREN.

PRODUCT

LU250 – SAE 10
LU251 – SAE 30
LU252 – SAE 50
LU253 – SAE 60



TO4 TRANSMISSION FLUID

- Excellent Thermal Stability
- Excellent Gear Protection
- Helps Extend Component Life
- Compatible with Crankcase Oil

KEEP OUT OF REACH OF CHILDREN
NET CONTENTS: 5 GAL (S)

FIRST AID

IF IN EYES: Flush with large amounts of water for at least 15 minutes or until irritation subsides.

IF ON SKIN: Remove any contaminated clothing and wash skin with soap and warm water.

IF INGESTED: Call physician immediately.

KEEP OUT OF REACH OF CHILDREN

CAS Numbers: Contains Petroleum Oil
(64742-54-7).

GHS: No GHS Pictograms

SIGNAL WORD: None

D.O.T. SHIPPING INFORMATION:
Not Considered DOT hazardous



BUY USA

Reorder LU250 - 253
800-548-2080

SOLD EXCLUSIVELY BY:


General Products & Supply Inc.

Murrysville Business Park
Export, PA 15632

HMIS RATING
1 - HEALTH
1 - FLAMMABILITY
0 - REACTIVITY
-- PROTECTIVE EQUIPMENT

GMP
Chemical Solutions

101 Technology Lane
(800) 548-2080