HYDRASPEC AW32 HYDRAULC Industrial Oils are premium quality lubricating oils designed to provide maximum protection against oxidation, corrosion and wear. They are formulated from highly refined high VI paraffinic base oils and carefully selected additives including anti wear, oxidation, and corrosion inhibitors, pour point, and a foam suppressant.

PRECAUTIONS

Misuse of empty containers can be hazardous. Empty containers can be dangerous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion, or toxic fumes from residue. Do not pressurize or expose to open flame or heat. Keep container closed and drum bungs in place. **KEEP OUT OF REACH OF CHILDREN.** Do not ingest.

This product contains petroleum oil (64742-54-7).

PRODUCT #LU401-55



HYDRASPEC AW Hydraulic/Industrial Oil ISO 32

- Demulsible
- High Oxidation Life
- Super Antiwear
- Noncoking

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 55 GAL(S)

HYDRASPECA W32 HYDRAULC Industrial Oils meet and exceed the performance requirements for Denison HF-0, HF-2; Cincinnati Milacron P-68, P-69, NP-70; Sperry Vickers 35, VQ25, Industrial and Mobile; API SA, SB, Motor Oils.

FIRST AID

IF IN EYES: Flush with clear water for at least 15 minutes or until irritation subsides.

IF ON SKIN: Remove any contaminated clothing and wash skin with soap and warm water. **IF INGESTED:** Call a physician immediately.

KEEP OUT OF REACH OF CHILDREN

GHS: No GHS Pictograms
SIGNAL WORD: None
D.O.T. SHIPPING INFORMATION:
Not Considered DOT hazardous

Reorder LU401 800-548-2080

SOLD EXCLUSIVELY BY:







Murrysville Business Park Export, PA 15632 101 Technology Lane (800) 548-2080