

**HYDRASPEC AW** Hydraulic/Industrial Oils are premium quality lubricating oils designed to provide maximum protection against oxidation, corrosion and wear. They are formulated from highly refined high VI paraffinic base oils and carefully selected additives including anti wear, oxidation, and corrosion inhibitors, pour point, and a foam suppressant. They are designed for use in high pressure or high speed vane and gear-type hydraulic pumps, rotary vane-type compressors, machine tools and circulating systems.

**HYDRASPEC AW** Hydraulic/Industrial Oils meet and exceed the performance requirements for Denison HF-0, HF-2; Cincinnati Milacron P-68, P-69, NP-70; Sperry Vickers 35, VQ25, Industrial and Mobile; API SA, SB, Motor Oils.

This product contains petroleum oil (64742-65-0).

**PRODUCT #LU402-55**



## **HYDRASPEC AW** **Hydraulic/Industrial Oil** **ISO 46**

- Demulsible
- High Oxidation Life
- Super Antiwear
- Noncoking

**KEEP OUT OF REACH OF CHILDREN**

NET CONTENTS: 55 GAL(S)

### **PRECAUTIONS**

Misuse of empty containers can be hazardous. Empty containers can be dangerous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion, or toxic fumes from residue. Do not pressurize or expose to open flame or heat. Keep container closed and drum bungs in place. Do no ingest.

### **FIRST AID**

**IF IN EYES:** Flush with clear water for at least 15 minutes or until irritation subsides.

**IF ON SKIN:** Remove any contaminated clothing and wash skin with soap and warm water.

**IF INGESTED:** Call a physician immediately.

### **KEEP OUT OF REACH OF CHILDREN**

**GHS:** No GHS Pictograms

**SIGNAL WORD:** None

**D.O.T. SHIPPING INFORMATION:**

Not Considered DOT hazardous

Reorder LU402  
800-548-2080

SOLD EXCLUSIVELY BY:

  
General Products & Supply Inc.

Murrysville Business Park  
Export, PA 15632

HMIS RATING
1 - HEALTH
1 - FLAMMABILITY
0 - REACTIVITY
-- PROTECTIVE EQUIPMENT

**GMP**  
Chemical Solutions

101 Technology Lane  
(800) 548-2080