

## MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA's Hazard Communication Standard CFR 1910.1200 and OSHA Form 174.

N/A SIGNIFIES NON-APPLICABLE

## IDENTITY AND SUPPLIERS INFORMATION

PRODUCT NAME:	ETERNABOND WEBSEAL 2"X50'	CHEMICAL FAMILY:												
GMP PRODUCT NUMBER:	RD971	FORMULA:	PROPRIETARY	<table><tr><th>NFPA HAZARDOUS MATERIALS IDENTIFICATION SYSTEM</th><th>RATING</th></tr><tr><td>HEALTH</td><td>0</td></tr><tr><td>FLAMMABILITY</td><td>1</td></tr><tr><td>REACTIVITY</td><td>0</td></tr><tr><td>MAX PERSONAL PROTECTION</td><td>-</td></tr></table>	NFPA HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	RATING	HEALTH	0	FLAMMABILITY	1	REACTIVITY	0	MAX PERSONAL PROTECTION	-
NFPA HAZARDOUS MATERIALS IDENTIFICATION SYSTEM	RATING													
HEALTH	0													
FLAMMABILITY	1													
REACTIVITY	0													
MAX PERSONAL PROTECTION	-													
SUPPLIER'S NAME:	GENERAL PRODUCTS & SUPPLY, INC.	PHONE NUMBER:	(724) 327-7200											
SUPPLIER'S ADDRESS:	101 TECHNOLOGY LANE	EMERGENCY NO.:	800-255-3924											
	EXPORT, PA 15632	DATE PREPARED:												
PROPER SHIPPING NAME:														

## SECTION 1 - INGREDIENT IDENTIFICATION AND INFORMATION

CHEMICAL NAME	CAS NO.	OSHA PEL	WT %	SARA III	PEL	TWA-TLV	ACGIH TLV
None							

## SECTION 2 - PHYSICAL/CHEMICAL PROPERTIES

BOILING POINT:	420° F
VAPOR PRESSURE: (mm Hg)	Not Applicable
VAPOR DENSITY:	Not Applicable
SOLUBILITY IN WATER:	Insoluble
SPECIFIC GRAVITY:	1.04 (adhesive)
pH RANGE:	
EVAPORATION RATE: (Ether=1)	Not Applicable
PHYSICAL DESCRIPTION:	Reinforced gray

## SECTION 3 - FIRE/EXPLOSION HAZARD DATA

FLAMMABILITY: (FLAME PROJECTION)	AUTO IGNITION TEMP:
FLASH POINT: 450°F COC	
FLAMMABILITY LIMITS: Not Applicable	%UEL: %LEL:
EXTINGUISHER MEDIA: Carbon dioxide, dry chemical, foam, water fog, and water spray	
SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool fire exposed surfaces and to protect personnel.	
UNUSUAL FIRE/EXP. HAZARDS:	

## SECTION 4 - REACTIVITY HAZARD DATA

STABILITY:	Stable
HAZARDOUS POLYMERIZATION:	Will Not Occur
INCOMPATIBILITY:	Avoid contact with strong oxidizing agents.
CONDITIONS TO AVOID:	Overheating
HAZARDOUS DECOMPOSITION PRODUCTS:	None

## SECTION 5 - HEALTH HAZARD DATA AND FIRST AID

PRIMARY ROUTES OF ENTRY:		FIRST AID PROCEDURES:	
ACUTE EFFECTS:		SKIN:	Remove with waterless hand cleaner. Wash with soap and water.
SKIN:	Not Applicable	EYES:	Flush with water.
EYES:	Not Applicable	INHALATION:	Not Applicable
INHALATION:	Not Applicable	INGESTION:	Contact a physician.
INGESTION:	Acute oral LD50 is greater than 10g/kg		

## SECTION 6 - CONTROL AND PROTECTIVE MEASURES

RESPIRATORY PROTECTION:	Not Applicable
PROTECTIVE GLOVES:	Not Applicable
EYE PROTECTION:	Chemical goggles
VENTILATION REQUIREMENTS:	Not Applicable
OTHER PROTECTIVE EQUIPMENT:	Not Applicable
HYGIENIC WORK PRACTICES:	Do not eat, drink or smoke in work area. Wash hands after handling. Launder contaminated clothing.

## SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:	Sweep up.
WASTE DISPOSAL METHODS:	Dispose of in accordance with Federal, State and Local regulations.
PRECAUTIONS IN HANDLING AND STORAGE:	Do not store near flame, heat or strong oxidizing agents.
OTHER PRECAUTIONS:	KEEP OUT OF REACH OF CHILDREN.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without any warranty or guarantee of any kind.